



## Inlube EP Gear Oil

### *Industrial Extreme Pressure Gear Oils*

**Inlube Industrial Gear Oils** are premium quality, extreme pressure, industrial gear lubricants designed for use in gears and bearings. These oils are designed to operate under severe service, heavy load and shock conditions. They are recommended for use in all types of enclosed industrial gear drives, bearings, chain and slides requiring extreme pressure gear oils and have extremely good antifoam characteristics and superior water separation.

**Inlube Industrial Gear Oils** satisfy most major industrial gear manufacturers' requirements, including AGMA 250.04, US Steel 224, and MIL-2105 specifications for extreme pressure gear lubes, as well as Cincinnati Milacron P-76, P-77, P-74, P-59 and P-35

#### Product Features:

- Extreme Pressure protection
- Good antifoam characteristics
- Superior water separation

#### Customer Benefits:

- Premium quality industrial gear lubricant
- For use in wide variety of enclosed industrial gear drives

#### Applications:

- Air compressors
- bearings
- gears
- low-pressure hydraulic systems

Specifications and Approvals	Inlube Industrial Gear oil
AGMA 250.04	✓
US Steel 224	✓
MIL-2105	✓
Cincinnati Milacron P-76, P-77, P-74, P-59 and P-35	✓



## Typical Properties

### Inlube Industrial Gear Oils

Product Number	280	281	282	283	284	Test Method
<b>ISO Grade (AGMA EP)</b>	46 (1EP)	68 (2EP)	100 (3EP)	150 (4EP)	220 (5EP)	-
<b>API</b>	30.53	30.1	30	29.23	28.41	-
<b>Specific Gravity</b>	0.873	0.876	0.876	0.880	0.885	ASTM 4052
<b>Lbs./Gal</b>	7.273	7.292	7.297	7.332	7.369	-
<b>Density</b>	0.872	0.875	0.875	0.879	0.884	-
<b>Flash Point °C</b>	221	230	236	250	265	ASTM D92
<b>Pour Point °C</b>	-27	-15	-15	-24	-18	ASTM D97
<b>Color</b>	<1.5	<1.0	<1.0	<2.0	<2.5	ASTM D1500
<b>Viscosity@ 100°C cSt</b>	6.35	8.7	11.34	14.9	19.1	ASTM D445
<b>Viscosity@ 40°C cSt</b>	46	68	100.6	150	220	ASTM D445
<b>Viscosity Index (VI)</b>	97	99	99	98	98	ASTM D2270

These properties are typical of the current production. Variations that do not affect product performance are to be expected depending on blending and manufacturing locations. The information above is subject to change without notice.

**Health and Safety:** This product is unlikely to have any adverse health implications or safety hazards when used for its intended application. Avoid contact with skin, use resistant gloves when handling used oil. If skin comes in contact wash immediately with soap and water. For complete information on safe handling and product characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website. [www.royalmfg.com](http://www.royalmfg.com) or call (918)-584-2671.

#### Packaging options:



55 Gal. Drums



275/330 Gal. Totes



>2,000 Gal. Bulk



## Typical Properties

Inlube Industrial Gear Oils					
Product Number	285	286	287	288	Test Method
ISO Grade (AGMA EP)	320 (6EP)	460 (7EP)	680 (8EP)	1000 (8AEP)	-
API	27.64	26.92	23.95	22.96	-
Specific Gravity	0.889	0.893	0.911	0.916	ASTM 4052
Lbs./Gal	7.405	7.44	7.581	7.629	-
Density	0.888	0.893	0.910	0.915	-
Flash Point °C	278	291	299	287	ASTM D92
Pour Point °C	-12	-9	3	-9	ASTM D97
Color	<3.0	<1.5	<2.0	<6.5	ASTM D1500
Viscosity@ 100°C cSt	25.63	31.13	37.35	44.51	ASTM D445
Viscosity@ 40°C cSt	342	462	702.6	1003	ASTM D445
Viscosity Index (VI)	98	98	88	82	ASTM D2270

These properties are typical of the current production. Variations that do not affect product performance are to be expected depending on blending and manufacturing locations. The information above is subject to change without notice.



**Health and****Safety:** This

55 Gal. Drums

275/330 Gal. Totes

&gt;2,000 Gal. Bulk

product is unlikely

to have any adverse health implications or safety hazards when used for its intended application. Avoid contact with skin, use resistant gloves when handling used oil. If skin comes in contact wash immediately with soap and water. For complete information on safe handling and product characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website. [www.royalmfg.com](http://www.royalmfg.com) or call (918)-584-2671

**Packaging options:**